## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Fatboy the Original B.V.
--------------------------------	--------------------------

Supplier's address: Fatboy the Original B.V., Het Zuiderkruis 3, 5215 MV 's-Hertogenbosch, NL

_	•			
Tyna	Λt	liaht	source	•
IVDC	VI.	HEIIL	<b>3</b> Uul CE	•

Type of light source.				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Connecting leads			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	
	General product p	arameters:		
Energy consumption in on-	2	Energy efficiency	F	

Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	mption in on- 100 h), rounded est integer	2	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode prespressed in W	oower (P <sub>on</sub> ),	1,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
for CLS, expres	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	42	Spectral power	See image
dimensions	Width	24	distribution in the	in last page
without	Depth	2		Page 1/3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity	0,463
		coordinates (x and y)	0,420
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

