## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Fatboy the Original B.V.

Supplier's address: Fatboy the Original B.V., Het Zuiderkruis 3, 5215 MV 's-Hertogenbosch, NL

Model identifier: Edison the Medium

Type	of	light	source:	
IVE	•	115116	Jour CC.	

Networked standby

cimal

Outer dimen-

sions without

separate con-

trol gear, lig-

(P<sub>net</sub>) for CLS, expressed in W

and rounded to the second de-

Height

Width

Depth

power

Lighting technology used:	LED	Non-directional or	NDLS
Light source cap-type	Integrated LED	directional:	
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	D
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	725 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 183
On-mode power (P <sub>on</sub> ), expressed in W	0,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the se-	0,00

cond decimal

set

140

140

50

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-

values that can be

Spectral power dist-

ribution in the range

250 nm to 800 nm,

at full-load

83

See image

in last page

hting control parts and non-lighting control parts, if any (millimetre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coord-	0,371			
		inates (x and y)	0,368			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	30	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

